



TECHNICAL BULLETIN

100 PLUS PAINT SEALANT

Range of Application:

Hydrophobic paint sealant for long term paint protection. The synthetic sponge gives a very regular spread over the painted surface.

WAXOYL AG, BASEL / SWITZERLAND
Phone +41 61 281 77 94 – Fax +41 61 281 77 85
E-mail: info@waxoyl.ch
www.waxoyl.com

100 PLUS PAINT SEALANT

1 APPLICATIONS

100 PLUS is a specially formulated paint sealant for long-term protection of painted surfaces. The protection of plastic material is also possible. As a consequence of the great variety of plastic materials, we recommend a test with **100 PLUS**.

2 PROPERTIES

Nature	Raw-white dispersion/emulsion sealed in a synthetic bag wrapped in a sponge.
Chemical character	Dispersion/emulsion of anorg. silicates, especially silicon-polymers, hydrocarbons, additives and water.
Solid contents 1 hour 120°C (248°F)	22 %
Density at 20°C (68°F)	0,92 - 0,99
Viscosity at 20°C (68°F) Rion Viscotester Rotor Nr. 3	420 - 500 cPs
Contents	89 ml / 84,6 g
Solvent	White Spirit, water
Shelf life	+ 5°C to + 38°C (41°F - 100°F), 2 years The product is not frost resistant! Store at temperatures above 0°C (32°F).

100 PLUS PAINT SEALANT

Processing temperature

+ 5°C to + 30°C (41°F - 86°F)

**Flashpoint
according to
DIN 53213**

44°C (111°F)

Congealing point

0°C. The product is not frost resistant.

DryingApprox. 15 min. at 20°C (68°F).
Force-drying is possible (drying conditions
must be discussed with Waxoyl!)

CoverageThe fill in a sponge is sufficient to seal
one car (8 - 10 m²).

Safety precautionsContains inflammable distillates
of mineral oil.
Keep away from fire and heat. Do not
ingest, dangerous to health! If ingested do
not attempt to vomit. Call medical
assistance immediately. Can cause eye
irritation. If in eyes, rinse immediately and
thoroughly with water. Do not inhale
fumes or vapours. Avoid long periods of
skin contact. Keep well away from
children. Wear gloves when using. Keep
work area well ventilated and, if
necessary, wear protective mask with
active carbon filter!

100 PLUS PAINT SEALANT

3 DIRECTIONS FOR USE

Application of 100 PLUS

Moisten the yellow side of sponge. Puncture the yellow side of sponge with pointed instrument. Using light pressure, distribute the content uniformly over the paintwork. It is important that the recommended quantity is applied (8 - 10m² per sponge). If too little is applied its effectiveness will be impaired. A uniform haze will remain after drying if applied correctly. When dry, remove this deposit using a clean cloth.

Preparation of the surface

To prevent scratches, the painted surfaces should be cleaned prior to application of **100 Plus**.

4 LIABILITY

The aforementioned information is based on our experience to the best of our knowledge. No guarantee can be given as to product data. The data shown here are typical values.

Technical changes reserved.
